



CSE Bliss Manufacturing, LLC.

P.O. Box 1332 Ponca City, Oklahoma U.S.A. 74602

Jason Bliss: (580)304-9432; Email: jason@csebliss.com

Rick Bliss: (580)716-2365; Email: rick@csebliss.com

Website: www.csebliss.com

CSE Bliss Rotary Feeder is designed to provide a steady, consistent supply of material across the full inlet of the Hammermill. This helps to achieve the hammermills full grinding capabilities. The rotary feeder requires a VFD to allow for adjustments of the feed rate to the hammermill. The CSE Feeder is designed to OUT LAST our competitor feeders and reduce down time. The CSE has sloped air inlets that allow air to flow directly into the hammermill.

The housing is made from 1/4" steel, and the inside that connects with the product is made of 3/8" steel. The 3/8" travels along the full circumference of the rotor, making all product contact areas last 2-3 times longer.

The CSE Feeder comes with a built-in magnet protection system. This system comes in two options as an mannual clamp unit or an auto self-clean unit. The built-in magnet protection system allows us to build the feeder to directly replace any other feeder on the market.

The CSE Feeder comes with Dodge bearings and sumitomo gear drives. We can offer TEFC or TEXP motors.

KEY FEATURES

- HEAVY DUTY MAGNET PROTECION
- SLOPED AIR INLETS (TO PREVENT PRODUCT BUILD UP)
- WELDED STEEL POCKET ROTOR
- 3/8" THICK STEEL PRODUCT CONTACT SURFACE
- AUTO MAGNET CLEANING

Optional Features:

- VFD
- Micro Switch to Indicate Magnet Open
- Heavy Duty Magnet
- High Intensity Magnet
- Rare Earth Magnet
- Explosion Proof Motor





