# **PRODUCT INSPECTION**



METAL DETECTORS OPTICAL INSPECTION SYSTEMS CHECKWEIGHERS SOFTWARE









The headquarters of Pulsotronic-Anlagentechnik GmbH are Niederdorf / Stollberg in the business district of Chemnitz - Zwickau, directly on the motorway A72 located. Here, all products "Made in Germany" are developed and manufactured in a modern building complex of more than 8,000 m<sup>2</sup> production area. The structural advantages, state-of-the-art production facilities and motivated employees prepare a top level of innovation and flexibility.

Pulsotronic plant technology is a pioneer in metal detection in the food, plastics and recycling industries. Other innovative products have been successful in the food industry. Based on many years of experience, Pulsotronic-Anlagentechnik develops, produces and sells metal detectors, end of line technology and special equipment. Since 2010 Pulsotronic-Anlagentechnik offers complete automation solutions in the product packaging area. Our Systems are characterized by their high reliability and ease of use. A team of engineers and specialists is constantly working on improvements and customized solutions. Through close cooperation with regional research institutes in Saxony, our products are always stateof-the-art. The development and production of all products and special equipment takes place completely at the Niederdorf site. This is it enable us to test new procedures and principles in the quickest possible way and put them into practice.

Quality assurance and environmental protection are central components of our management. Pulsotronic system technology closes in all respects, the "ZVEI Code of Conduct" on social responsibility.

Do you not find the product you are looking for in the brochure? Do you need a custom solution? Do you have any questions or suggestions? Our sales engineers will gladly advise you on site.

Our sales engineers are happy to advise you on site.








## **Performance Overview**

Comprehensive technical knowledge and excellent on-site service are prerequisites for a successful machinery and equipment business. We are happy to tackle your tasks and remain true to our slogan:

### "Pulsotronic - complex solution from one source"







We offer a wide range of evaluation electronics, which are specially adapted to our sensors. This achieves maximum sensitivity and reliability. All electronics have a very good handling and a simple user interface and can be extended as needed.

Hardweit 1 4006-018 1008     Image: Control of Cont	M-Pulse3 • multi-siumtaneous frequency technology / multiscan technology • touch screen / graphical display 7" / detached • high-precision product effect offsetting • unlimited product memory spaces • Network / Ethernet / USB / remote control/support • comprehensive support for peripherals
	M-Pulse2
Market 2: 01.2 2014 10.950: generated     **       Image: State of the sta	<ul> <li>four-quadrant technology / multi-frequency technology</li> <li>touch screen / graphical display 5,7" / detached</li> <li>high-precision product effect offsetting</li> <li>unlimited product memory spaces</li> <li>Network / Ethernet / USB / remote control/support</li> <li>comprehensive support for peripherals</li> </ul>
	Digital2
DIGTAL 2	<ul> <li>primarily intended for use with bulk materials detectors</li> <li>high-precision product effect offsetting</li> <li>six product memory spaces</li> <li>easily operation by 3.5" TFT</li> </ul>
	MESEP
p·u·l·s·o· <mark>t·r·o·n·i·c</mark>	intended for use with bulk materials detectors

· easy operation



ON

TEST OO

•

ME7ES

STANDARD



**METAL DETECTORS - TUNNEL** for conveyor, chutes and foils / roll goods

M-Pulse2

### Complete device BD + HQ



- hygienic design
- · highest sensitivity
- customized special model
- many options available
- · fulfills all the requirements according to HACCP / IFS
- · link chain or polyurethane belt (PU)

 high level of detection since the magnetic field surrounds the products

M-Pulse3

IP65

IP69k

IP54

Ethernet

· multi-simultaneous frequency technology available

M-Pulse2

- optionally available in multi-frequency technology
- stainless steel housing with long-time stable and water-tight encapsulation

Digital2

- · available in various detector sizes, adapted for the product
- · fulfills all the requirements according to HACCP / IFS
- hygienic design

**BD** - series

many sizes available



#### TU - series

- · devidable stainless steel housing
- · available in various detector sizes, adapted for the product
- · easy integration into existing systems





IP54

### SP / AR - series

- · easily integrated in conveyor belts, since it can be installed flush
- · long-term stable, fully encapsulated in extremely stable metal housing
- · belt stop or reverse motion operation available using reversing contactor circuitry
- external control electronics with RESET/START-STOP button
- standard detection widths to 1,200 mm
- no metal-free zones necessary

### **FS** - series

- · especially for sorting tasks in the recycling industry
- integrated controller for discharge elements (blast pipe or pushers)

FS HMI

IP65

IP

Ethernet


- · can be controlled via optional operating unit, SPC or PC
- · available in models with various resolutions and widths
- · standard detection widths to 2,000 mm (alignable sensors for bigger total widths on inquiry)
- · no metal-free zones necessary

#### **FL** - series

- flat pick-up coil for mounting under a belt conveyor or chute
- · available in various sensor widths, adapted to the product
- · stainless steel housing with long-time stable and water-tight encapsulation

Digital2









6



### **GF / GFC - series**



 open, easily accessible precious metal rack, also available in compact styles

Digital2

- device-specific material throughput of up to 200,000 l/h
- · optionally with special wear-resistant ejection unit
- · product-touching parts made of stainless steel/POM

ő pulse traite

### **VA - series**

· extremely sturdy and compact stainless steel housing

Digital2

M-Pulse2

HT 200°C

HT 200°C

IP54

Ethernet

 device-specific material throughput from 14,000 l/h of up to 40,000 l/h

MESEP

- · stainless steel ejection unit
- · optionally with wear-resistant product pipe
- · optionally high-temperature application



### **Y** - series

- extremely effective, quick-reacting pneumatic outward transfer system
- · separates metal also from slow back-pressure material columns
- · device-specific material throughput of up to 5,400 l/h

Digital2

- · extremely flat mounting height
- · optionally high-temperature application



7



### **Compact series**

- · ultra-compact design
- · maintenance-free separation system only for bulk materials

Digital2

HT 200°C

Ethernet

IP54

- · device-specific up to 5,400 l/h material throughput
- · compressed-air ejection

**SE** - series

· optionally high-temperature application

· extremely sturdy and compact aluminium housing

- · device-specific material throughput of up to 14,000 l/h
- · extremely quick-responding ejection unit made of stainless steel

Digital2

M-Pulse2

IP54

IPE

Eth

MESEP

IP54



### **Extraktor series**

- · unique ejection system for integration in suction conveyor the pipe system
- · remains closed during the ejection of metal impurity!
- · easily integrated into the suction conveyor line with hose connection
- · adjustment-free separating, irrespective of material speed

Digital2

- · device-specific material throughput of up to 3,300 l/h
- · optionally in wear-resistant model

MESEP







·O·t·r·o·n·i·c





### GFS - series

- compact design
- sensitivity for ferrous metals and non-ferrous metals from 0,6 mm

Digital2

Digital2

M-Pulse2

IP54

MESEP

IP54


Ethernet

IP65

- · calibration free
- · various sizes and types available
- · designed for installation in flow wrapping machines
- powerful electronic with product effect offsetting
- protection class IP65
- connection via Ethernet


#### **RG** - series

- compact design
- diameter 20 .. 100 mm
- sensitivity for ferrous and nonferrous metals up to 0,2 mm
- calibration free
- · powerful electronic with product effect offsetting



#### **KJR** - series

- wide delivery range, ring diameters from 6 mm to 300 mm
- plastic or metal housing
- · integrated evaluation electronics with signal exit





### **Inline Series**

- · easily integrated in pipeworks
- with flexible or rigid, high pressure-resistant pipe connection adapters

M-Puls

IP6

Ethernet

- various separating valves available (butterfly, arc valve)
- with CIP (Clean-In-Process) function



### **Inflex Series**



• available for all usual machines (e.g. Vemag, Handtmann, Frey, Risco, Rex)

M-Pulse2

M-Pulse3

IP69k

Ethernet

- simple integration adapters for the most common sausage filler models
- · optional ejection valves / wring-off
- · easy dismantling for cleaning
- with CIP (Clean-In-Process) function
- · ejection monitoring



## **CHECKWEIGHER / OPTICAL INSPECTION**

CW3

IP65

for conveyors

### **Checkweigher CW3**



- · easy operation & clear visualisation
- calibratable / calibrated available
- HACCP, IFS-compliant logging
- · simple to integrate into existing systems
- · option to integrate calibration-free metal detector
- custom platform sizes, weighing zone and conveyor speeds f
  ür all applications
- · all components made from stainless steel
- hygiene concept



· customer styled combination of metal detector and checkweigher



**Optical inspection OI2** 

IP54 Etherne

Ethernet




- universal optical testing system
- suitable for rigid and flexible film packaging
- packaging inspected on both sides (label, MHD, EAN, seal seam)
- HACCP, IFS-compliant logging
- · simple to integrate into existing systems






#### Central network solution "UniControl"

- · central data capture and analysis
- any number of users (multi-user system)
- data stored in an SQL server database
- · connection to BDE or PP systems
- · Webbased user interface
- suitable for Windows, IOS, Android or Linux (user interface)







### **SPECIAL MACHINES** for end-of-line solutions

### **Converger PV - series**

- · compact efficient universal
- · well suited for all thermoforming machines
- machine interface OPCUA
- different models available
- up to 17 cycles/minute

#### **Packaging machine PM - series**

- · secondary packaging machine for trays and thermoformed packs
- semi automated machines for simple application up to fully automated solutions available

Servo

Servo

PLC

IP65

OPCUA

PLC

- up to 160 products/minute
- · enormous rationalization potential with short ROI

### **Conveyor HQ - series**

- all sizes and lengths with PU- or link chain belt available
- · equipped with controlled and energy-efficient drives
- · special solutions with numerous options and accessories
- · elevating conveyors / curved belts / tilting belts and much more
- made from stainless steel









### Service



#### • free telephone hotline

- · broad network of distributors for on-site service
- VPN-Connection
- updates for soft- and firmware avaiable
- annual testing service according HACCP / IFS
- large spare part inventory

### **Advice & Service**

#### · expert advice - by telephone and on-site

- design and construcion of customer's design and 3D-models
- · loan units and devices for demonstration
- product tests





### **Contact - Sales**

### **Germany / International**

Tel.: +49 (0) 37296 / 9383 524 Fax.: +49 (0) 37296 / 9383 521 Email: sales@pulsotronic-anlagentechnik.de

Inquiries and information will be forwarded to our internal sales and service partners by our head office. Please see also our website www. pulsotronic-anlagentechnik.de for more details.



### North America Distributor:




#### **Scan American Corporation**

9505 N. Congress Ave Kansas City, MO 64153-1811

Phone: +1 (816) 880-9321

www.scanamcorp.com | info@scanamcorp.com



Please see our homepage to contact our international service and sales partners!

### Sales Germany / International Headquarters

Pulsotronic-Anlagentechnik GmbH Neue Schichtstr. 7 D-09366 Niederdorf

Phone: +49 37296 9383-500 Fax: +49 37296 9383-501

info@pulsotronic-anlagentechnik.de www.pulsotronic-anlagentechnik.de





ISO 14001:2015 / ISO 9001:2015

