


## PRODUCT SPECIFICATIONS

<b>PRODUCT CODE/POF</b>	
<b>PRODUCT NAME</b>	RECYCLABLE MONO PE
<b>VERSION NUMBER</b>	
<b>VERSION EXPLANATION</b>	
<b>STRUCTURE</b>	PE 50 $\mu$ / PE WHITE 70 $\mu$
<b>PRINT</b>	FLEXO
<b>CUSTOMER</b>	

PE 50 $\mu$   
PRINT  
ADHESIVE  
PE WHITE 70 $\mu$



PROPERTIES	TEST CONDITION	VALUES
<b>TOTAL WEIGHT</b>	TA-PKL 075	121g/m <sup>2</sup> $\pm$ % 5
<b>CUT-OFF LENGTH</b>	TA-PKL-001	N/A
<b>ROLL WIDTH</b>	TA-PKL-001	N/A
<b>CORE DIAMETER</b>	TA-BSK-299	N/A
<b>ROLL OUTER DIAMETER</b>	TA-BSK-299	N/A
<b>COF INSIDE INSIDE</b>	PP KG-TA-052	<0,30
<b>COF OUTSIDE OUTSIDE</b>	PP KG-TA-052	<0,40

### KrcPack Headquarter

Akçaburgaz Mah. Muhsin Yazıcıoğlu 2. Cad. No: 43  
Esenyurt / İSTANBUL  
0(212) 465 69 00 (PBX)  
0(212) 465 69 03  
info@krcpack.com

### İzmir Office

Kazım Dirik Mah. 364/1 Avcılar Effect B225  
Bornova/İZMİR  
info@krcpack.com

24/06/2019  
krcpack.com

## SHELF LIFE

Generally we inform 6 months shelf life for Cold seal / Hotmelt / Thermolacquer or packaging includes lacquer over side, and 1 year for the heat seal packaging in the content of suitable stocking conditions. We suggest customer to use the material under control of evaluation craters which passes this period.

## SUITABLE STOCKING CONDITIONS

- Suitable environment temperature 15°-30° C - relative humidity 45-55% is advised for the material which includes BOPP, CPP, PET, PE, Paper, BOPA, Alu
- It is advised to protect the material with KrcPack packaging format.
- Material should be protected from humidity.
- Pallets and rolls should not be closer to direct heat source and direct sun light in the stocking area. Otherwise it will be a reason to change the physical characteristics such as breaking .blowing of the material, COF and finally this effects machine performance.
- Before production, packaging material should be taken to the production area previously and roll temperature should be conditioned to the environment temperature. This period should be minimum 24 hours in very cold winter season. Temperature and relative humidity is valid on production conditions
- 'First In First Out' rule is suggested for consumption of Packaging Material.
- These conditions should also be provided for the packaging material which includes Cold Seal / Thermolacquer / Hotmelt

## FOOD CONTACT



Above mentioned material complies with the requirements of Turkish Food Codex; EU Regulation (EC) 1935/2004 and Regulation No 10/2011 EU on materials and articles intended to come into contact with food. Specific documentation and/or test results are available upon request.

The information given in this data sheet is to the best of KrcPack professionals' knowledge and experience and intended to give general information on our products and their applications. It is confidential and therefore, it should not be given to third parties under any circumstances, either expressed or implied. As the conditions for the use of our products are beyond our control, the information and recommendations given are not covered under warranty and we disclaim liability for any loss or damage that may occur from the use of this information. Some of the properties can be changed as a result of suppliers' efforts to improve upon the quality or production efficiency of the subject. We suggest purchasers to contact to check suitability for specific end uses.



### **KrcPack Headquarter**

Akçaburgaz Mah. Muhsin Yazıcıoğlu 2. Cad. No: 43  
Esenyurt / İSTANBUL  
0(212) 465 69 00 (PBX)  
0(212) 465 69 03  
info@krcpack.com

### **İzmir Office**

Kazım Dirik Mah. 364/1 Avcılar Effect B225  
Bornova/İZMİR  
info@krcpack.com

24/06/2019  
krcpack.com