

## **COOL-FIT® PE Plus**

## Pre-insulated system for refrigeration and chilled water



# Safe, efficient cooling has never been easier!

COOL-FIT® is the successful range of pre-insulated plastic piping systems from GF Piping Systems. It makes cooling applications more efficient than before—in all phases of your project. COOL-FIT® simplifies planning and installation through superior design, pre-insulation, low weight, and modern jointing technologies. COOL-FIT® reduces costs through completely maintenance free operation, energy efficiency, and longevity (more than 25 years). COOL-FIT® is environmentally friendly, thanks to its low carbon dioxide emissions, throughout the entire service life of the product. The specialists at GF Piping Systems support you in this through all project phases.



**Electrofusion fitting** 

## **100%** maintenance-free

Fully plastic media pipe—corrosion and scaling free. UV resistant and corrosion-free jacket pipe. Preinsulated with closed cell insulation attached to both media and jacket pipes. Fully vaportight system that can be power washed—no degradation of insulation due to water uptake.

### **65%** less weight

Makes perfect use for buildings with challenging load bearings. In rooftop installations, this weight reduction can allow for more equipment to be installed on the roof, increasing the commercial floor space available. The robustness of hangers and supports can be downsized.

### **50%** quicker installation

Less time required on site. Complete control of the installation schedule—3 in 1 system. Machine controlled electrofusion jointing reduces human error to an absolute minimum and allows for traceability of the joints.

### **30 %** higher energy efficiency

Thanks to the low thermal conductivity of plastic pipes compared to metal and the superior insulation properties of the foam insulation ( $\lambda \le 0.015$  BTU/hR.Ft.F) The COOL-FIT® system is significantly more energy efficient than any other systems. How much? Our free calculation tool can help you calculate.



## **Product features**



### Pre-insulated pipes for fast installation

No post insulation steps are necessary with the COOL-FIT® PE Plus system result in significant time savings. Additionally, the lightweight makes moving pipe and fittings around the job sites easier, safer and faster



### Wide range of pre-insulated electrofusion fittings

The offering of COOL-FIT® PE Plus fittings includes elbows, tees, couplers, and reducers. Electrofusion ensures permanent joints in just a few minutes.



### Valves

Both ball and butterfly valves are available in the COOL-FIT® PE Plus system. Easy to use insulation kits are available and have options for electric and pneumatic actuation.



### **Uncomplicated flange connections**

Connection to existing metal systems is simple with the use of flange connections. The COOL-FIT® PE Plus range includes ANSI 150# flange adaptors and a matching insulation kit for a clean, consistent install.



### Instrument fittings for sensors

Sensors for measuring pressure, temperature, and other parameters can be easily integrated with our threaded instrument fittings.



### Easy transitions to metal systems

The COOL-FIT® PE Plus adapter fittings enable simple transitions to metal connections, allowing for effortless solutions to adjacent systems.



### **Tools and training**

GF Piping Systems offers a complete range of tools for purchase or rent and provides factory certified training to ensure proper procedures are understood and followed.



### **COOL-FIT® PE Plus**

## Leading technology for easy installation and longevity

COOL-FIT® PE Plus is the result of years of development by our engineers with the aim of making the system even easier and faster to install, while at the same time, remaining as safe, reliable, and durable as you expect from all GF Piping Systems solutions. Many crucial details contribute to this.

### COOL-FIT® 4.0

Materials *	Media pipe	HDPE
	Insulation	PUR
	Outer jacket	Pipe: HDPE, Fitting: Plasticized PUR
Dimensions		1" - 18" (d32 - d450)
Joining technology		Electrofusion
Max Pressure		1" – 4" (d32 - d110) SDR 11 200 PSI
		6" – 18" (d160-d450) SDR 17 130 PSI
Temperature		Media -58ºF - 140ºF Ambient -22ºF - 140ºF
Weight		Pipe 1" (d32) 0.95 lb/ft
(without liquid)		Pipe 8" (d225) 11.1 lb/ft
Environment	Resistance	Water- and vapor-tight; UV resistant
	Ozone depleting potential	Zero
Standards	EN ISO 15494	Plastic piping systems for industrial applications – Metric series
	ISO 7	Fittings
	EN ISO 16135, EN ISO 16138	Industrial valves

\* All three materials are permanently connected.





# Machine controlled jointing process-in just minutes

COOL-FIT® PE Plus pipes, fittings, and valves can be connected neatly, easily, and within just a few minutes by electrofusion. Our specialists show the installation team how it's done, both on site and in a detailed video tutorial – step by step.

One of the most significant benefits of COOL-FIT® PE Plus is clean, simple, and fast installation. The installation team can easily interconnect pipes, fittings, and valves within just a few minutes, thanks to the exceptional design and the use of electrofusion. The pipe ends are already peeled when delivered, meaning that the installation can start without delay. The sealing lip of the fitting along with the vulcanizing tape seals the insulation without any additional work. Even installers without any previous electrofusion experience find it easy to install COOL-FIT<sup>®</sup> PE Plus . We provide onsite training and certification free of charge.



Clean the fusion zones of the fitting and pipe using Tangit  $\ensuremath{\mathsf{PE}}\xspace$ -cleaner and a clean paper towel.



Place the assembly aid on the fitting. Stretch the sealing lip pressing the handles together.



Slide both ends of the pipe into the fitting as far as the marking. Then remove the assembly aid.



Connect the welding cables to the welding contacts of the fitting and weld according to the instruction manual.

### Watch the installation tutorial video: www.gfps.com/cf4-installation

### **GF Piping Systems**

Our sales companies and representatives ensure local customer support in over 100 countries.

Argentina / Southern South America Georg Fischer Central Plastics Sudamérica S.R.L. Buenos Aires, Argentina Phone +54 11 4512 02 90 gfcentral.ps.ar@georgfischer.com www.gfps.com/ar

### Australia

George Fischer Pty Ltd Riverwood NSW 2210 Australia Phone +61 (0) 2 9502 8000 australia.ps@georgfischer.com www.gfps.com/au

### Austria

Georg Fischer Rohrleitungssysteme GmbH 3130 Herzogenburg Phone +43 (0) 2782 856 43-0 austria.ps@georgfischer.com www.gfps.com/at

Belgium / Luxembourg Georg Fischer NV/SA 1070 Bruxelles/Brüssel Phone +32 (0) 2 556 40 20 be.ps@georgfischer.com www.gfps.com/be

### Brazil

Georg Fischer Sist. de Tub. Ltda. 04795-100 São Paulo Phone +55 (0) 11 5525 1311 br.ps@georgfischer.com www.gfps.com/br

### Canada

Georg Fischer Piping Systems Ltd Mississauga, ON L5T 2B2 Phone +1 (905) 670 8005 Fax +1 (905) 670 8513 ca.ps@georgfischer.com www.gfps.com/ca

### China

Georg Fischer Piping Systems Ltd Shanghai 201319 Phone +86 21 3899 3899 china.ps@georgfischer.com www.gfps.com/cn

Denmark / Iceland Georg Fischer A/S 2630 Taastrup Phone +45 (0) 70 22 19 75 info.dk.ps@georgfischer.com www.gfps.com/dk

Finland Georg Fischer AB 01510 VANTAA Phone +358 (0) 9 586 58 25 Fax +358 (0) 9 586 58 29 info.fi.ps@georgfischer.com

www.gfps.com/fi

France Georg Fischer SAS 95932 Roissy Charles de Gaulle Cedex Phone +33 (0) 1 41 84 68 84 fr.ps@georgfischer.com www.gfps.com/fr

Germany Georg Fischer GmbH 73095 Albershausen Phone +49 (0) 7161 302-0 info.de.ps@georgfischer.com www.gfps.com/de

India Georg Fischer Piping Systems Ltd 400 076 Mumbai Phone +91 224007 2001 branchoffice@georgfischer.com www.gfps.com/in

### Indonesia George Fischer Pte Ltd – Representative Office Phone +62 21 2900 8564 Fax +62 21 2900 8566 sgp.ps@georgfischer.com www.gfps.com/sg

Italy Georg Fischer S.p.A. 20063 Cernusco S/N (MI) Phone +39 02 921 861 it.ps@georgfischer.com www.gfps.com/it

#### Japan Georg Fischer Ltd 556-0011 Osaka, Phone +81 (0) 6 6635 2691 jp.ps@georgfischer.com www.qfps.com/jp

Korea GF Piping Systems Georg Fischer Korea Co., Ltd. Unit 2501, U-Tower 120 HeungdeokJungang-ro (Yeongdeok-dong) Giheung-gu, Yongin-si, Gyeonggi-do, Korea Phone: +82 31 8017 1450 Fax : +82 31 8017 1450 Kor.ps@georgfischer.com www.gfps.com/kr

### Malaysia

George Fischer (M) Sdn. Bhd. 40460 Shah Alam, Selangor Darul Ehsan Phone +60 (0) 3 5122 5585 Fax +603 5122 5575 my.ps@georgfischer.com www.gfps.com/my Mexico / Northern Latin America Georg Fischer S.A. de C.V. Apodaca, Nuevo Leon CP66636 Mexico Phone +52 (81) 1340 8586 Fax +52 (81) 1522 8906 mx.ps@georgfischer.com www.gfps.com/mx

Middle East Georg Fischer Piping Systems (Switzerland) Ltd Dubai, United Arab Emirates Phone +971 4 289 49 60 gcc.ps@georgfischer.com www.gfps.com/int

Netherlands Georg Fischer N.V. 8161 PA Epe Phone +31 (0) 578 678 222 nl.ps@georgfischer.com www.gfps.com/nl

Norway Georg Fischer AS 1351 Rud Phone +47 67 18 29 00 no.ps@georgfischer.com www.gfps.com/no

Philippines George Fischer Pte Ltd Representative Office Phone +632 571 2365 Fax +632 571 2368 sgp.ps@georgfischer.com www.gfps.com/sg

Poland Georg Fischer Sp. z o.o. 05-090 Sekocin Nowy Phone +48 (0) 22 31 31 0 50 poland.ps@georgfischer.com www.gfps.com/pl

Romania Georg Fischer Piping Systems (Switzerland) Ltd 020257 Bucharest - Sector 2 Phone +40 (0) 21 230 53 80 ro.ps@georgfischer.com www.gfps.com/int

### Russia Georg Fischer Piping Systems (Switzerland) Ltd Moscow 125047 Phone +7 495 258 60 80 ru.ps@georgfischer.com www.gfps.com/ru

Singapore George Fischer Pte Ltd 11 Tampines Street 92, #04-01/07 528 872 Singapore Phone +65 6747 0611 Fax +65 6747 0577 sgp.ps@georgfischer.com www.gfps.com/sg

Spain / Portugal Georg Fischer S.A. 28046 Madrid Phone +34 (0) 91 781 98 90 es.ps@georgfischer.com www.gfps.com/es

 Sweden
 Georg Fischer AB

 117 43 Stockholm
 Phone +46 (0) 8 506 775 00

 info.se.ps@georgfischer.com
 www.gfps.com/se

Switzerland Georg Fischer Rohrleitungssysteme (Schweiz) AG 8201 Schaffhausen Phone +41 (0) 52 631 30 26 ch.ps@georgfischer.com www.gfps.com/ch

Taiwan Georg Fischer Co., Ltd San Chung Dist., New Taipei City Phone +886 2 8512 2822 Fax +886 2 8512 2823 www.gfps.com/tw

United Kingdom / Ireland George Fischer Sales Limited Coventry, CV2 2ST Phone +44 (0) 2476 535 535 uk.ps@georgfischer.com www.gfps.com/uk

USA / Caribbean Georg Fischer LLC 9271 Jeronimo Road Irvine, CA 92618 Phone +1 714 731 88 00 Fax +1 714 731 62 01 us.ps@georgfischer.com www.gfps.com/us

#### International Georg Fischer

Piping Systems (Switzerland) Ltd 8201 Schaffhausen/Switzerland Phone +41 (0) 52 631 30 03 Fax +41 (0) 52 631 28 93 info.export@georgfischer.com www.gfps.com/int

### Contact us

Tel. (714) 731-8800, Toll Free (800) 854-4090 Fax (800) 426-7188 us.ps@georgfischer.com www.gfpiping.com



Item #1378 (3/19) © 2019 Georg Fischer LLC Printed in USA